

Module: preferences

Module: preferences

Method	Parameters	HTTP Method	Description	URL Example
addBookmark	String path	GET/ POST	Adds a filepath bookmark	http://localhost:8080/AppvanceServer/rest/preferences/addBookmark?path=path
createDB		GET/ POST	Creates database results repository	http://localhost:8080/AppvanceServer/rest/preferences/createDB
deleteAppDynamics	String name		Delete an AppDynamics config	
deleteBookmark	String path	GET/ POST	Delete a bookmark	http://localhost:8080/AppvanceServer/rest/preferences/deleteBookmark?path=path
deleteDynaTrace	String name	GET/ POST	Delete a dynaTrace config	http://localhost:8080/AppvanceServer/rest/preferences/deleteDynaTrace?name=name
deleteNewRelic	String repositoryName	GET/ POST	Delete a new relic configuratin	http://localhost:8080/AppvanceServer/rest/preferences/deleteNewRelic?name=name
deleteRepository	String repositoryName	GET/ POST	Delete repository with the provided repository name.	http://localhost:8080/AppvanceServer/rest/preferences/deleteRepository?name=repositoryName
deleteRepositoryByUser	String repositoryName, String utpUserName	GET/ POST	Delete repository with the provided repository name based on a particular user.	http://localhost:8080/AppvanceServer/rest/preferences/deleteRepositoryByUser?name=name&utpusername=username
downloadJiraSettings			Download Jira Settings	

Method	Parameters	HTTP Method	Description	URL Example
getAllRepositoryByUser	String username		Returns repository names from AIQ UserName	
getAPMConfigurations			Gets the names of NewRelic and DynaTrace Configuration Names	
getAppDynamicsConfiguration	String name		Gets a newRelic configuration details by name	
getAppDynamicsConfigurationNames			Returns AppDynamics names	
getAppDynamicsConfigurations			Gets the AppDynamics Configurations	
getBookmarks		GET/ POST	Returns bookmarks	http://localhost:8080/AppvanceServer/rest/preferences/getBookmarks
getBranches	String username, String name	GET/ POST	Get list branches	http://localhost:8080/AppvanceServer/rest/preferences/getBranches?username=username&name=RepositoryVal
getBrowsers			Gets the browsers	
getDBStatus			Tests database connection	
getDS3Port		GET/ POST	Gets the ds3ports	http://localhost:8080/AppvanceServer/rest/preferences/getDS3Port
getDynaTraceConfiguration	String name	GET/ POST	Gets a dynaTrace configuration details by name	http://localhost:8080/AppvanceServer/rest/preferences/getDynaTraceConfiguration?name=configName
getDynaTraceConfigurationNames		GET/ POST	Returns dyna trace names	http://localhost:8080/AppvanceServer/rest/preferences/getDynaTraceConfigurationNames
getDynaTraceConfigurations		GET/ POST	Gets the DynaTrace Configurations	http://localhost:8080/AppvanceServer/rest/preferences/getDynaTraceConfigurations

Method	Parameters	HTTP Method	Description	URL Example
getGitRepositoryAuthor	String username, String name		Returns repository author	
getJiraSettings			Gets Jira settings	
getLatestTimeRefreshRepositories		GET/ POST	Get Latest Time Refresh Repositories	http://localhost:8080/AppvanceServer/rest/preferences/getLatestTimeRefreshRepositories
getLoadRunnerPath		GET/ POST	Gets Load Runner Path	http://localhost:8080/AppvanceServer/rest/preferences/getLoadRunnerPath
getNewRelicConfiguration	String name	GET/ POST	Gets a newRelic configuration details by name	http://localhost:8080/AppvanceServer/rest/preferences/getNewRelicConfiguration?name=newRelicConfigVal
getNewRelicConfigurationNames		GET/ POST	Returns new relic names	http://localhost:8080/AppvanceServer/rest/preferences/getNewRelicConfigurationNames
getNewRelicConfigurations		GET/ POST	Gets the NewRelic Configurations	http://localhost:8080/AppvanceServer/rest/preferences/getNewRelicConfigurations
getNotifications		GET/ POST	Checks notifications preferences	http://localhost:8080/AppvanceServer/rest/preferences/getNotifications
getRepository	String name	GET/ POST	Return repository details based on the repo name.	http://localhost:8080/AppvanceServer/rest/preferences/getRepository?name=repoName
getRepositoryByUser	String name, String utpUserName	GET/ POST	Returns repository names by individual users.	http://localhost:8080/AppvanceServer/rest/preferences/getRepositoryByUser?name=repoName&utpusername=username
getRepositoryNames		GET/ POST	Returns all repository names	http://localhost:8080/AppvanceServer/rest/preferences/getRepositoryNames

Method	Parameters	HTTP Method	Description	URL Example
getRepositoryNamesByUser	String utpUserName	GET/ POST	Returns all repository names based on users.	http://localhost:8080/AppvanceServer/rest/preferences/getRepositoryNamesByUser?utpusername=username
getRepositoryPath			allows to get repositories settings	
getRepositoryStatus	String RepositoryName	GET/ POST	Returns repository status	http://localhost:8080/AppvanceServer/rest/preferences/getRepositoryStatus?name=repoName
getResultRepository		GET/ POST	Gets database results repository preferences	http://localhost:8080/AppvanceServer/rest/preferences/getResultRepository
getSahi		GET/ POST	Gets sahi configuration	http://localhost:8080/AppvanceServer/rest/preferences/getSahi
getScenarios			Gets previous scenarios	
getSchema		GET/ POST	Gets database schema	http://localhost:8080/AppvanceServer/rest/preferences/getSchema
pullRepository	String username, String name	GET/ POST	Pull current repository	http://localhost:8080/AppvanceServer/rest/preferences/pullRepository?name=repoName
refreshRepositories			Force refresh repositories	
saveAppDynamicsConfiguration	JSONObject config		Save a AppDynamics configuration	
saveBrowsers			Saves the browsers list	
saveDS3Port	JSONObject ds3Ports, String username	GET/ POST	save DS3 port	http://localhost:8080/AppvanceServer/rest/preferences/saveDS3Port?http=9090&https=9091

Method	Parameters	HTTP Method	Description	URL Example
saveDynaTraceConfiguration	JSONObject configuration	GET/ POST	Save a DynaTrace configuration	http://localhost:8080/AppvanceServer/rest/preferences/saveDynaTraceConfiguration?name=relicName&url=url&id=id&dashboard=dashboard
saveJiraSettings			Save Jira preferences	
saveLoadRunnerPath	JSONObject obj	GET/ POST	Save LoadRunner Path preferences	http://localhost:8080/AppvanceServer/rest/preferences/saveLoadRunnerPath?path=path
saveNewRelicConfiguration	JSONObject newRelic	GET/ POST	Save New Relic configurations.	http://localhost:8080/AppvanceServer/rest/preferences/saveNewRelicConfiguration?name=relicName&url=url&id=id&dashboard=dashboard
saveNotifications	JSONObject obj	GET/ POST	Checks notifications preferences	http://localhost:8080/AppvanceServer/rest/preferences/saveNotifications?mailuser=username&mailuserpassword=password&mailhost=host&mailport=port&sslvalue=boolean
saveRepository	JSONObject repository	GET/ POST	Save new or updates existing valid repository.	http://localhost:8080/AppvanceServer/rest/preferences/saveRepository //please see below sample saveRepository JSON
saveRepositoryCommitMessage	String username, String repositoryName, String commitMessage		Save new or updates existing valid repository.	
saveResultsRepository	final JSONObject obj	GET/ POST	Saves database results repository preferences	http://localhost:8080/AppvanceServer/rest/preferences/saveResultsRepository////please see below sample saveResultsRepository JSON

Method	Parameters	HTTP Method	Description	URL Example
saveSahi	JSONObject obj	GET/ POST	Gets sahi configuration	http://localhost:8080/AppvanceServer/rest/preferences/saveSahi?path=path&mustrun=boolean
testConnection		GET/ POST	Tests database connection	http://localhost:8080/AppvanceServer/rest/preferences/testConnection
testConnectionParams	JSONObject config	GET/ POST	Tests database connection based on params	http://localhost:8080/AppvanceServer/rest/preferences/testConnectionParams?username=name&password=password&engine=resultType&url=repoURL
testJiraSettings			Test Jira Settings	
testQuery	String quer	GET/ POST	Tests query	http://localhost:8080/AppvanceServer/rest/preferences/testQuery?query=sqlVal

Sample:

```

var repository = {
    type: $('#repositoryType').val(),
    name: $('#repositoryName').val(),
    url: $('#repositoryURL').val(),
    username: $('#repositoryUsername').val(),
    ssh: ssh,
    auth: $('#repositoryAuth').val(),
    password: password,
    utpusername: username,
    branch: $("#reposList").val() == undefined ? "master" : $("#reposList").val()
};

saveResultsRepository
var result = {
    username: $('#resultsUsername').val(),
    password: $('#resultsPassword').val(),

```

```
engine: $("#resultsType").val(),
url: $('#resultsURL').val(),
database: $('#resultsDatabase').val(),
maxActive: $('#resultsMaxActive').val(),
maxIdle: $('#resultsMaxIdle').val(),
maxWait: $('#resultsMaxWait').val(),
abandonedTimeout: $('#resultsRemoveAbandonedTimeout').val(),
autoCommit: $('#resultsAutoCommit').prop('checked'),
logAvandoned: $('#resultsLogAbandoned').prop('checked'),
removeAvandoned: $('#resultsRemoveAbandoned').prop('checked'),
enabled: $('#resultsEnabled').prop('checked')
};
```

Revision #1

Created 2026-07-24 14:30:39 UTC by Admin

Updated 2026-07-24 14:30:39 UTC by Admin