

Test Designer HTTP history functions

_setHistory

Parameters: value

Description: sets the history file which is a zip containing all requests.

Example:

```
“ FileClient fs = new FileClient();  
  fs.setHistory("test/com/appvance/ds/js/cecris/DSLog_NewPRF.zip");
```

_replayHistory

Description: playback the history file

Example:

```
“ _replayHistory();  
  _wait(2000);  
  _navigateTo("https://g-mmember-qa1.example.in/");
```

_clearHistory

Description: clears the history data

Example:

```
_clearHistory();  
_stopHistory();
```

_stopHistory

Description: stops playing the history

Example:

```
““ FileClient fs = new FileClient();  
try{  
    fs.setHistory("test/com/appvance/ds/js/ppd/DSLog.zip");  
    fs.replayHistory();  
    fs.processJSFile("test/com/appvance/ds/js/ppd/getAttr.js");  
} finally {  
    fs.clearHistory();  
    fs.stopHistory();  
}
```

_dontCheckForWS

Parameters: DNS, port

Description: adds the domain and host to the list of domains that should not be checked for HTTPS connection.

Example:

```
““ _dontCheckForWS(" g-mmemberr-qa1.copart.in ",443);  
_dontCheckForWS(" cdn.polyfill.io ",443);  
_dontCheckForWS(" smetrics.copart.com ",443);  
_wait(10000);  
_navigateTo(" https://g-mmemberr-qa1.copart.in/");  
_wait(1000);  
_click(_div("AUCTIONS"));
```

_printAssertions

Parameters: boolean

Description: enables logging of assertions executed. Mainly used for debugging purposes.

Example:

```
// _printAssertions(true);
```

Revision #1

Created 2026-07-24 14:33:13 UTC by Admin

Updated 2026-07-24 14:33:13 UTC by Admin