

How to handle Multiple DPL files in Test Designer IDE

We can add multiple DPL files in Test Designer IDE. Once the user adds one of the DPL files in Data tab User can still add other DPL files if any with the help of API that is already available for Hash DPL and JS DPL.

File Options Edit Scripts Hash_DPL.ds Record Play Pause Stop Step Over				
No	Action	Accessor	Value	Description
1	Add Hash DPL	"{ds}/Hash1.csv"		
2	Add JS DPL	"{ds}/JS.csv"		
3	Log	\$FirstName		
4	Log	\$Date		
5	Log	\$Name		

With the help of the above API called “Add Hash DPL” and “Add JS DPL”. User can add multiple DPL’s in the IDE.

Below is the screenshot for the successful execution of the same

File Options Edit Scripts Hash_DPL.ds Record Play Pause Stop Step Over				
No	Action	Accessor	Value	Description
1	Add Hash DPL	"{ds}/Hash1.csv"		
2	Add JS DPL	"{ds}/JS.csv"		
3	Log	\$FirstName		

Logs Data Checkpoint Relational Accessors				Logs
<pre>Processing \$FirstName = "First";* Step 1:* log("\$Name = "XYZ";*") Step 2:* log("\$Date = "2022/09/28";*") Step 3:* log("First") Step 4:* log("2022/09/28") Step 5:* log("XYZ") Playback Completed Successfully.</pre>				

Last updated: June 26, 2023

If you have any feedback on this topic, please contact us at documentation@appvance.ai

Revision #4

Created 2026-07-31 15:40:05 UTC by Admin

Updated 2026-10-14 14:05:16 UTC by AI_Mananger