Special Character value to be replaced in HAR script

This article contains the values of special characters that needs to be replaced in HAR script

There are some special characters in HAR which are used as their original form like .(dot) , _(underscore) and so on. For other special character whose values have to replaced have been mentioned below along with the ones whose values remains same

1) ,(comma)= %2C(the Value of comma should be replaced with %2C. The same logic applies to all the below values)
2) .=.(dot values to dot)
3) /=%2F(Forward slash values to %2F)
4) <=%3C(Less than values to %3C)
5) >=%3E(Greater than values to %3E)
6) ?=%3F(Question mark values to %3F)
7) ;=%3B(Semi colon values to %3B)
8) '='(Apostrope values to Apostrophe)
9) :=%3A(Colon values to %3A)
10) "=%22(Quotation values to %22)
11) `=%60(Back tick values to %60)
12) ~=~(Tilde values to Tilde)
13) !=!(Exclamation values to Exclamation)
14) @=%40(At sign values to %40)
15) #=%23(Hash values to %23)
16) $=%24(Dollar values to %24)
17) %=%25(Perecnt values to %25)
18) ^=%5E(Caret values to %5E)
19) &=%26(Ampersand values to %26)
20) *=* (star values to star)
21))=) (Right open bracket values to Right open bracket)
22) (=)(Left open bracket values to left open bracket)
23) _=_(underscore values to underscore)
24) +=%2B(Plus values to %2B)
25) -=- (Minus values to minus)
26) "="=%3D(Equals to values to %3D)
27) [=%5B(Left open square bracket values to %5B)
28)]=%5D(Right open square bracket values to %5D)
29) \=%5C(Backward slash values to %5C)
30) {=%7B(left open flower bracket values to &7B)

31) }=%7D(right open flower bracket values to %7D)
32) |=%7C(Vertical bar values to %7C)

33) Space is equivalent to "+"(addition symbol)

Last updated: October 15, 2026

If you have any feedback on this topic, please contact us at documentation@appvance.ai

---

Revision #3
Created 2026-07-31 15:37:57 UTC by Admin
Updated 2026-10-15 23:02:38 UTC by mmora